

# SPECIFICATION DATA

Suitable for use on a range of building projects, including traditional and contemporary. Can be used in conjunction with Siberian Larch Cladding (specified separately). Please note that the product will weather to a silver-grey if left untreated.



## APPROVALS

- FSC® certified.
- Durability class 3 according to BS EN 350-2.

## REFERENCE

- **Siberian Larch Decking**

## FEATURES

- Density: 570–650 kg/m<sup>3</sup>.
- Recommended fixings: Millfix™, Specifically manufactured stainless-steel fixings, available in secret, face-fix or clip systems, are designed for Millworks timber cladding and decking profiles.

## GRADES

- 1.B (Sawfalling) Larger knots, high durability. BS 1186-3 Class 2.

## PROFILES

- MW-D21 I Grooved. Depth: 21 mm.
- MW-D21 II Smooth. Depth: 21 mm.
- MW-D26 I Grooved. Depth: 26 mm.
- MW-D26 II Smooth. Depth: 26 mm.

## FINISHES & TEXTURES

- Factory finished: clear UV, OrganoWood® (silver/ grey) or RAL (any colour)
- Burnt and factory finished
- Burnt
- Fine-sawn
- Planed

## BOARDS

- Board size:Width: 143 mm.Length: Consult manufacturer for details

## FIRE - TREATMENT

- Fire retardant treatment (FRX Exterior). Complies with the National Building Regulations where Euroclass B or C fire performance is required.

+44(0)1223 967733 | [info@millworks.co.uk](mailto:info@millworks.co.uk)

Millworks LTD | Parsonage Barns | Bottisham | Cambridge | CB25 9EG