

SPECIFICATION DATA

Suitable for use on a range of building projects, including traditional and contemporary. Can be used in conjunction with Western Red Cedar Cladding (specified separately). Please note that the product will weather to a silver-grey if left untreated.



APPROVALS

- PEFC™ certified.
- Durability class 2 according to BS EN 350-2.

REFERENCE

- **Western Red Cedar Decking**

FEATURES

- Density: 390 kg/m³.
- Recommended fixings: Millfix™, Specifically manufactured stainless-steel fixings, available in secret, face-fix or clip systems, are designed for Millworks timber cladding and decking profiles.

GRADES

- No. 2 Clear and Better - High quality. Limited knots. This results in a consistent, seamless appearance.
- No. 2 Clear and Better (15% No. 4) - Combination of grades. Allows the aesthetically pleasing pieces to be prominently placed.
- No. 4 Clear - Larger and a higher amount of knots.

PROFILES

- MW-D21 I Grooved. Depth: 21 mm.
- MW-D21 II Smooth. Depth: 21 mm.

FINISHES & TEXTURES

- Factory finished: clear UV, OrganoWood® (silver/ grey) or RAL (any colour)
- Burnt and factory finished
- Burnt
- Fine-sawn
- Planed

BOARDS

- Board size: Width: 143 mm. Length: Consult manufacturer for details

FIRE - TREATMENT

- Fire retardant treatment (FRX Exterior). Complies with the National Building Regulations where Euroclass B or C fire performance is required.

+44(0)1223 967733 | info@millworks.co.uk

Millworks LTD | Parsonage Barns | Bottisham | Cambridge | CB25 9EG