

# SPECIFICATION DATA

Suitable for use on a range of building projects, both traditional and contemporary. Can be used in conjunction with Millworks® Siberian Larch Decking (specified separately). Please note that the product will weather to a silver-grey if left untreated.



## APPROVALS

- FSC® certified. Millworks certification no. INT-COC-003944.292
- Durability class 3 according to BS EN 350-2.

## REFERENCE

- **Millworks® Siberian Larch**

## FEATURES

- Density: 570–650 kg/m<sup>3</sup>.
- Recommended fixings: Millfix™, Specifically manufactured stainless-steel fixings, available in secret-fix, face-fix or clip systems, are designed for Millworks® timber cladding and decking profiles. These systems can be written into the NBS H21 specification.

## GRADES

- Millworks® Siberian Larch Grade A = High quality, limited knots. Offers a clean, consistent look. BS 1186-3 Class 2.
- Millworks® Siberian Larch Grade B = Larger knots, high durability. BS 1186-3 Class 2.

## PROFILES

- MW-1, MW-2, MW-5, MW-6, MW-7, MW-8, MW-11, MW-12 I, MW-12 II, MW-12 III and custom profiles available when specified.

## TEXTURES & COATINGS

- Planed
- Brushed
- Burned & Brushed
- Fine-sawn
- Milltex®
- Factory coated: Translucent UV Protection , OrganoWood® (consistent silver- grey) or any RAL colour.

## TRIMS & LENGTHS

- 20 x 43mm, 20 x 93mm, 20 x 143mm, 44 x 44mm, 44 x 93mm.
- Lengths up to 5.1m.
- Finger jointed up to 12m upon request.

## FIRE - TREATMENT

- Fire retardant treatment (FRX Exterior). Complies with the National Building Regulations where Euroclass B or C fire performance is required.
- Coating to RAL (any colour) maintains FRX fire certification.

+44(0)1223 967733 | [info@millworks.co.uk](mailto:info@millworks.co.uk)

Millworks LTD | Parsonage Barns | Bottisham | Cambridge | CB25 9EG