

SPECIFICATION DATA

PEFC™ certified Thermowood® (Redwood) cladding. Carefully selected from leading Finnish sawmills and suitable for use on a range of external building projects. Please note that the product will weather to a silver-grey if left untreated.



APPROVALS

- PEFC™ certified.
- Durability class 2 according to BS EN 350-2.

REFERENCE

- **Millworks® Thermowood® (Redwood) Cladding**

FEATURES

- Density: 420 kg/m³.
- Recommended fixings: Millfix™, Specifically manufactured stainless-steel fixings, available in secret, face-fix or clip systems, are designed for Millworks® timber cladding and decking profiles.

GRADES

- Millworks® A/B Thermowood® (Thermo D) where D stands for durability, has a darker brown tone. Its durability and stability are improved significantly.

PROFILES

- MW-1, MW-2, MW-5, MW-6, MW-7, MW-10 and custom profiles available when specified..

FINISHES & TEXTURES

- Factory finished: clear UV, OrganoWood® (silver/ grey) or RAL (any colour)
- Planed
- Brushed

TRIMS

- 20 x 43mm, 20 x 93mm, 20 x 143mm, 44 x 44mm, 44 x 93mm.
- Lengths up to 5.4m.

FIRE - TREATMENT

- Fire retardant treatment (FRX Exterior). Complies with the National Building Regulations where Euroclass B or C fire performance is required.
- Coating to RAL (any colour) maintains FRX fire certification.

+44(0)1223 967733 | info@millworks.co.uk

Millworks LTD | Parsonage Barns | Bottisham | Cambridge | CB25 9EG