

SPECIFICATION DATA

Suitable for use on a range of building projects, including traditional and contemporary. Can be used in conjunction with Millworks® Western Red Cedar Decking (specified separately). Please note that the product will weather to a silver-grey if left untreated.



APPROVALS

- PEFC™: Certificate: PEFC/16-37-2002.
- Durability class 2 according to BS EN 350-2.

REFERENCE FEATURES	<ul style="list-style-type: none">• Millworks® Western Red Cedar Cladding
GRADES	<ul style="list-style-type: none">• Density: 390 kg/m³.• Recommended fixings: Millfix™, Specifically manufactured stainless-steel fixings, available in secret-fix, face-fix or clip systems, are designed for Millworks® timber cladding and decking profiles. These systems can be written into the NBS H21 specification.• No. 2 Clear and Better = High quality. Limited knots. This results in a consistent, seamless appearance.• No. 2 Clear and Better (15% No. 4) = Combination of grades. Allows the aesthetically pleasing pieces to be prominently placed.• No. 2 Clear and Better, Vertical Grain (VG) = Hand graded and 'quarter sawn' to produce growth rings in a vertical orientation.• No. 4 Clear = Larger and a higher amount of knots.
PROFILES	<ul style="list-style-type: none">• MW-1, MW-2, MW-5, MW-6, MW-7 and custom profiles available when specified.
TEXTURES & COATINGS	<ul style="list-style-type: none">• Planed• Burned & Brushed• Milltex®• Factory coated: Translucent UV Protection, OrganoWood® (consistent silver/ grey).
TRIMS	<ul style="list-style-type: none">• 20 x 43mm, 20 x 93mm, 20 x 143mm, 44 x 44mm, 44 x 93mm.• Lengths up to 4.88m.
FIRE - TREATMENT	<ul style="list-style-type: none">• Fire retardant treatment (FRX Exterior). Complies with the National Building Regulations where Euroclass B or C fire performance is required.• Coating to RAL (any colour) maintains FRX fire certification.

+44(0)1223 967733 | info@millworks.co.uk

Millworks LTD | Parsonage Barns | Bottisham | Cambridge | CB25 9EG